

## Cube 04

---

---



Resourceful, discreet multipurpose LED downlight. Recessed. Low-glare. Each head tilts 30° in all directions. For indoor use. For area, room, display, surface and task lighting. Easy installation in any ceiling. Xicato LED technology. Choice of CCT, lumen and beam angle combinations. Minimum 50% energy saving compared to equivalent halogen. Light quality ensured for entire lifetime. Rigorously tested. Rigorously documented. The light you specify is the light you get.

## Cube 04

For indoor use/dry locations

Recessed

Die-cast aluminium/steel

Tilts 30° in all directions

Position lock

Low-glare

Operating ambient temperature -20° to +40°

3,000 K or 4,000 K

Beam angle 20° or 40°

1, 2 and 3-head models also available

Trimless models also available

Non-dimming drivers included

Dimming drivers available

Xicato LED technology

CRI (Ra) 80 or 95

Five-year warranty

LED standard lifetime 50,000 hours

LED luminous flux 1000 or 2000 lm

Fixture luminous efficacy 40 to 50 lm/W

**4.2 kg**  
1000 lm

**3.9 kg**  
2000 lm



**IP 20**

**238x238mm**

**30°**

RoHS   

## Cube 04



**Item no.**

White	20°	3,000 K	Ra 95	1000 lm	C0493010NW
		4,000 K	Ra 80	2000 lm	C0484020NW
	40°	3,000 K	Ra 95	1000 lm	C0493010MW
		4,000 K	Ra 80	2000 lm	C0484020MW

By special order: other combinations of beam angle + CCT + Ra + lumen

Full, current photometric data and product documentation available at [www.roblonlighting.com](http://www.roblonlighting.com)

Roblon accepts no responsibility for possible errors in catalogues, brochures or other printed and electronic material. Roblon reserves the right to alter or discontinue its products without notice. © 2012, Roblon A/S | 050312