



H2 Pro

Firerated LED dimming down light

Product data

Product code	DLP38XXXXDIM	DLP60XXXXDIM
Colours available (LED)	NW & WW	NW & WW
Colours available (Fascia)	White, chrome, silver, polished gold, black & brushed steel	
	All fascias are available in round and square (brushed steel: round only)	

Photometrics

Beam angle (°)	38		60	
Colour temperature (K)	±175k			
CRI (color rendering index)	R8			
Life of LED (hrs)	L70, B10			
Luminous flux (lm)	NW: 550	WW: 470	NW: 550	WW: 470
Wattage (W)	8.5		8.5	
Luminous efficacy (lm/w)	NW: 65	WW: 55	NW: 65	WW: 55
Lux @ 1m	NW: 1723	WW: 1127	NW: 361	WW: 284

Wiring

Drivers	N/A (700mA LED dimmable driver built in)
Cable/flying lead (mm)	150
Type of wiring required	Parallel (mains)
Power factor	>0.95

General

Accessories	DM GRID 500 (Dimmer). DL/M/DIM EMERGENCY PACK. DL/CONVERT 70 (Large hole adapter)
Bathroom zone	1
Construction material (body)	ABS, ALU, MS & PP
Cut-out (mm)	60-70
Building regulations	B,C,E,L & P
Face temperature when lit (°C)	35
IP rating	65
Rotation angle (°)	N/A
SELV (safety extra low voltage)	Yes
Tilt angle (°)	N/A
Warranty (yrs)	1 (7 year extended warranty available)
Weight (Kg)	0.5