SPECIFICATION SHEET





H2 Lite LED down light

	57.5mm
Ø105/157mm	

Product data

Product coc	e	
Colours ava	ilable (LED)	
Colours ava	ilable (Fascia)	

DL280XXXX

DLCONVERT 63

Parallel (mains) >0.95

150

Neutral White (NW) & Warm White (WW) White (WH), chrome (CR) & brushed steel (BS)

N/A (700mA non dimmable LED driver built in)

Photometrics

Beam angle (°)	
Colour temperature (K)	±175k
CRI (color rendering index)	R8
Life of LED (hrs)	L70, B10
Luminous flux (lm)	
Wattage (W)	
Luminous efficacy (lm/w)	
Lux ն 1m	

38 NW: 4000 WW: 3000 NW: 70 WW: 85 70,000 NW: 450 WW: 330 7.9 WW: 42 NW: 57 NW: 1400 WW: 1100

Wiring

Accessories
Drivers
Cable/flying lead (mm)
Type of wiring required
Power factor

Ge	ne	

Bathroom zone
Construction material (body)
Cut-out (mm)
Building regulations
Face temperature when lit (°C)
IP rating
Rotation angle (°)
SELV (safety extra low voltage)
Tilt angle (°)
Warranty (yrs)
Weight (Kg)

1
Steel / aluminium
65-92
B,C,E,L & P
50
65
N/A
Yes
N/A
1 (7 year extended warranty available)
0.3



All data quoted is subject to change without prior notice.



