



H5 500 Symmetric

Recessed low glare down light

Product data

Product code	DL284
Colours available (LED)	3SDCM Neutral white & Warm white
Colours available (Bezel)	White, Chrome & Brushed steel

Photometrics

Beam angle (°)	40
Colour temperature (K)	NW: 4000 WW: 3000 ±175k
CRI (colour rendering index)	NW: 70 WW: 85 R8
Life of LED (hrs)	70,000 L70, B10
Luminous flux (lm)	NW: 550 WW: 470
Wattage (W)	8.5
Luminous efficacy (lm/w)	NW: 65 WW: 55
Lux @ 1m	NW: 1267 WW: 1125

Wiring

Accessories	DM GRID 500
Dimming	Leading and trailing edge mains dimmable
Drivers	N/A (700mA LED driver built in) Class II
Cable/flying lead (mm)	150
Type of wiring required	Parallel
Power factor	0.95

General

Accessories	LEDEP05 & DL CONVERT 98
Bathroom zone	1
Construction material (body)	Aluminium / Steel
Cut-out (mm)	95-115
Building regulations	B,C,E,L & P
Face temperature when lit (°C)	40
IP rating	65
Rotation angle (°)	N/A
SELV (safety extra low voltage)	Yes
Tilt angle (°)	N/A
Warranty (yrs)	1 (7 year extended warranty available)
Weight (Kg)	0.3

All data quoted is subject to change without prior notice