

Single 01



Simple, small, hard-working, all-purpose LED downlight. Recessed. Low-glare. For indoor use. For area, room and surface lighting and many other applications. Easy installation in any ceiling. Xicato LED technology. Choice of CCT, lumen and beam angle combinations. Minimum 50% energy saving compared to equivalent halogen. Light quality ensured for entire lifetime. Rigorously tested. Rigorously documented. The light you specify is the light you get.

Single 01

For indoor use/dry locations
 Recessed
 Die-cast aluminium/plastic
 Low-glare
 Operating ambient temperature -20° to +40°
 2,700 K, 3,000 K or 4,000 K
 Beam angle 40° or 60°
 Outdoor/wet location models also available
 Non-dimming driver included
 Dimming drivers available
 Xicato LED technology
 CRI (Ra) 80 or 95
 Five-year warranty
 LED standard lifetime 50,000 hours
 LED luminous flux 1000 or 1300 lm
 Fixture luminous efficacy 37 to 52 lm/W

0.61 kg
1300 lm


0.90 kg
1000 lm

IP 20

Ø97 mm

RoHS  

Single 01



						Item no.
White	40°	3,000 K	Ra 95	1000 lm	S0193010MW	
			Ra 80	1300 lm	S0183013MW	
		4,000 K	Ra 95	1000 lm	S0194010MW	
			Ra 80	1300 lm	S0184013MW	
	60°	2,700 K	Ra 95	1000 lm	S0192710WW	
			Ra 80	1300 lm	S0183013WW	
		3,000 K	Ra 95	1000 lm	S0193010WW	
			Ra 80	1300 lm	S0183013WW	
4,000 K	Ra 95	1000 lm	S0194010WW			
	Ra 80	1300 lm	S0184013WW			

By special order: other combinations of beam angle + CCT + Ra + lumen