

Single 02



Simple, small, hard-working, all-purpose LED downlight. For outdoor and wet locations. Recessed. Low-glare. For lighting areas and surfaces. For bathrooms, balconies, canopies, entrances, passageways and many other applications. Easy installation in any ceiling. Xicato LED technology. Choice of CCT and lumen combinations. Minimum 50% energy saving compared to equivalent halogen. Light quality ensured for entire lifetime. Rigorously tested. Rigorously documented. The light you specify is the light you get.

Single 02

For outdoor use/wet locations
 Recessed
 Die-cast aluminium/plastic
 Low-glare
 Operating ambient temperature -20° to +40°
 3,000 K
 Beam angle 60°
 Indoor models also available
 Non-dimming driver included
 Dimming drivers available
 Xicato LED technology
 CRI (Ra) 80 or 95
 Five-year warranty
 LED standard lifetime 50,000 hours
 LED luminous flux 1000 or 1300 lm
 Fixture luminous efficacy 39 to 52 lm/W

0.68 kg
1300 lm


0.96 kg
1000 lm

IP 54
from front

Ø97 mm

RoHS  

Single 02



Item no.

White	60°	3,000 K	Ra 80	1300 lm	S0283013WW
			Ra 95	1000 lm	S0293010WW

By special order: other combinations of beam angle + CCT + Ra + lumen