

## Single 03

---

---



Compact, effective, adjustable LED downlight. Recessed. Shallow mounting. Tilts 33°. For indoor use. For area, room and surface lighting. For wall-washing and many other applications. Easy installation in any ceiling. Xicato LED technology. Choice of CCT, lumen and beam angle combinations. Minimum 50% energy saving compared to equivalent halogen. Light quality ensured for entire lifetime. Rigorously tested. Rigorously documented. The light you specify is the light you get.

## Single 03

For indoor use/dry locations  
 Recessed  
 Tilts 33°  
 Die-cast aluminium/plastic  
 Operating ambient temperature -20° to +40°  
 3,000 K or 4,000 K  
 Beam angle 40° or 70°  
 Non-dimming driver included  
 Dimming drivers available  
 Xicato LED technology  
 CRI (Ra) 80 or 95  
 Five-year warranty  
 LED standard lifetime 50,000 hours  
 LED luminous flux 1000 or 1300 lm  
 Fixture luminous efficacy 36 to 57 lm/W

0.53 kg


IP 20

Ø93 mm

33°

RoHS  

## Single 03



						Item no.
White	40°	3,000 K	Ra 95	1000 lm	S0393010MW	
			Ra 80	1300 lm	S0383013MW	
	70°	3,000 K	Ra 80	1300 lm	S0384013MW	
			Ra 95	1000 lm	S0393010WW	
		4,000 K	Ra 80	1300 lm	S0383013WW	
			Ra 95	1000 lm	S0384013WW	

By special order: other combinations of beam angle + CCT + Ra + lumen