

## Single 06

---

---



Simple, powerful, all-purpose LED downlight. Recessed. Long throw distance. For indoor use. For area, room and surface lighting and many other applications. Easy installation in any ceiling. Xicato LED technology. Choice of CCT and beam angle combinations. Minimum 50% energy saving compared to equivalent halogen. Light quality ensured for entire lifetime. Rigorously tested. Rigorously documented. The light you specify is the light you get.

## Single 06

---

For indoor use/dry locations  
Recessed  
Die-cast aluminium/plastic  
Operating ambient temperature -20° to +40°  
3,000 K or 4,000 K  
Beam angle 40° or 70°  
Non-dimming driver included  
Dimming drivers available  
Xicato LED technology  
CRI (Ra) 80  
Five-year warranty  
LED standard lifetime 50,000 hours  
LED luminous flux 2000 lm  
Fixture luminous efficacy 45 to 51 lm/W

0.81 kg


IP 20

Ø122 mm

RoHS   

## Single 06

---



						Item no.
White	40°	3,000 K	Ra 80	2000 lm	S0683020MW	
		4,000 K	Ra 80	2000 lm	S0684020MW	
	70°	3,000 K	Ra 80	2000 lm	S0683020WW	
		4,000 K	Ra 80	2000 lm	S0684020WW	

By special order: other combinations of beam angle + CCT + Ra + lumen