

Single 07



Simple, powerful, all-purpose LED downlight. Recessed. Tilts 30°. Rotates 355°. Long throw distance. For indoor use. For area, room and surface lighting. For wall-washing and many other applications. Easy installation in any ceiling. Xicato LED technology. Choice of CCT and beam angle combinations. Minimum 50% energy saving compared to equivalent halogen. Light quality ensured for entire lifetime. Rigorously tested. Rigorously documented. The light you specify is the light you get.

Single 07

For indoor use/dry locations

Recessed

Tilts 30°

Rotates 355°

Die-cast aluminium/plastic

Operating ambient temperature -20° to +40°

3,000 K or 4,000 K

Beam angle 20° or 60°

Non-dimming driver included

Dimming drivers available

Xicato LED technology

Five-year warranty

CRI (Ra) 80 or 95

LED standard lifetime 50,000 hours

LED luminous flux 1000 and 2000 lm

Fixture luminous efficacy 40 to 50 lm/W

0.86 kg
2000 lm

0.91 kg
1000 lm

IP 20


Ø121 mm

30°

355°

RoHS   

Single 07



						Item no.
White	20°	3,000 K	Ra 95	1000 lm	S0793010NW	
			Ra 80	2000 lm	S0783020NW	
		4,000 K	Ra 95	1000 lm	S0794010NW	
			Ra 80	2000 lm	S0784020NW	
	60°	3,000 K	Ra 95	1000 lm	S0793010WW	
			Ra 80	2000 lm	S0783020WW	
		4,000 K	Ra 95	1000 lm	S0794010WW	
			Ra 80	2000 lm	S0784020WW	

By special order: other combinations of beam angle + CCT + Ra + lumen