

Single 08



Smart, discreet all-purpose LED downlight. Recessed. Low-glare. Tilts 30°. Rotates 355°. For indoor use. For area, room and surface lighting and many other applications. Easy installation in any ceiling. Xicato LED technology. Choice of CCT, lumen and beam angle combinations. Minimum 50% energy saving compared to equivalent halogen. Light quality ensured for entire lifetime. Rigorously tested. Rigorously documented. The light you specify is the light you get.

Single 08

For indoor use/dry locations
 Recessed
 Die-cast aluminium/plastic
 Tilts 30°
 Rotates 355°
 Low-glare
 Operating ambient temperature -20° to +45°
 3,000 K or 4,000 K
 Beam angle 20° or 60°
 Oval and square models also available
 Non-dimming driver included
 Dimming drivers available
 Xicato LED technology
 CRI (Ra) 80 or 95
 Five-year warranty
 LED standard lifetime 50,000 hours
 LED luminous flux 1000, 1300 or 2000 lm
 Fixture luminous efficacy 40 to 55 lm/W

1.0 kg
1300/2000 lm

0.8 kg
1000 lm

IP 20


Ø121mm

30°

355°

RoHS CE 

Single 08



						Item no.
White	20°	3,000 K	Ra 95	1000 lm	S0893010NW	
			Ra 80	1300 lm	S0883013NW	
			Ra 80	2000 lm	S0883020NW	
	4,000 K	Ra 95	1000 lm	S0894010NW		
		Ra 80	1300 lm	S0884013NW		
		Ra 80	2000 lm	S0884020NW		
	60°	3,000 K	Ra 95	1000 lm	S0893010WW	
			Ra 80	1300 lm	S0883013WW	
			Ra 80	2000 lm	S0883020WW	
4,000 K		Ra 95	1000 lm	S0894010WW		
		Ra 80	1300 lm	S0884013WW		
		Ra 80	2000 lm	S0884020WW		

By special order: other combinations of beam angle + CCT + Ra + lumen