

Single 09



Smart, discreet all-purpose LED downlight. Recessed. Low-glare. Tilts 30°. Rotates 355°. For indoor use. For area, room and surface lighting and many other applications. Easy installation in any ceiling. Xicato LED technology. Choice of CCT, lumen and beam angle combinations. Minimum 50% energy saving compared to equivalent halogen. Light quality ensured for entire lifetime. Rigorously tested. Rigorously documented. The light you specify is the light you get.

Single 09

For indoor use/dry locations

Recessed

Die-cast aluminium/plastic

Tilts 30°

Rotates 355°

Low-glare

Operating ambient temperature -20° to +45°

3,000 K or 4,000 K

Beam angle 20° or 60°

Round and square models also available

Non-dimming driver included

Dimming drivers available

Xicato LED technology

CRI (Ra) 80 or 95

Five-year warranty

LED standard lifetime 50,000 hours

LED luminous flux 1000 or 2000 lm

Fixture luminous efficacy 40 to 50 lm/W

0.95 kg
2000 lm

1.0 kg
1000 lm

IP 20


Ø121mm

30°

355°

RoHS  

Single 09



						Item no.
White	20°	3,000 K	Ra 95	1000 lm	S0993010NW	
			Ra 80	2000 lm	S0983020NW	
	4,000 K	Ra 95	1000 lm	S0994010NW		
		Ra 80	2000 lm	S0984020NW		
60°	3,000 K	Ra 95	1000 lm	S0993010WW		
		Ra 80	2000 lm	S0983020WW		
	4,000 K	Ra 95	1000 lm	S0994010WW		
		Ra 80	2000 lm	S0984020WW		

By special order: other combinations of beam angle + CCT + Ra + lumen