

Single 11



Powerful, adjustable LED downlight. Recessed. Tilts 45°. 3000 lumen. Long throw distance. For indoor use. For wall-washing. For task and display lighting. For area, room and surface lighting and many other applications. Easy installation in any ceiling. Xicato LED technology. Choice of CCT. Minimum 50% energy saving compared to equivalent halogen. Light quality ensured for entire lifetime. Rigorously tested. Rigorously documented. The light you specify is the light you get.

Single 11

For indoor use/dry locations
 Recessed
 Tilts 45°
 Die-cast aluminium/plastic
 Safety glass
 Operating ambient temperature -20° to +40°
 3,000 K or 4,000 K
 Beam angle 80°/95°
 Non-dimming driver included
 Dimming drivers available
 Xicato LED technology
 CRI (Ra) 80
 Five-year warranty
 LED standard lifetime 50,000 hours
 LED luminous flux 3000 lm
 Fixture luminous flux 53 lm/W

1.82 kg



IP 20

218x136 mm

45°

RoHS  

Single 11



Item no.

White	80°/95°	3,000 K	Ra 80	3000 lm	S1183030WW
		4,000 K	Ra 80	3000 lm	S1184030WW

By special order: other combinations of beam angle + CCT + Ra + lumen

Full, current photometric data and product documentation available at www.roblonlighting.com

Roblon accepts no responsibility for possible errors in catalogues, brochures or other printed and electronic material. Roblon reserves the right to alter or discontinue its products without notice. © 2012, Roblon A/S | 010212