

## Track 01

---

---



Precise, powerful, flexible, all-purpose LED spotlight. Track-mounted. Choice of beam angles. Low-glare. Tilts 90°. Rotates 355°. For indoor use. For defining both collective displays and individual objects, often together. For lighting areas, rooms and surfaces. Easy installation in any ceiling. Xicato LED technology. Choice of CCT, lumen and beam angle combinations. Minimum 50% energy saving compared to equivalent halogen. Light quality ensured for entire lifetime. Rigorously tested. Rigorously documented. The light you specify is the light you get.

## Track 01

For indoor use/dry locations  
 Track-mounted  
 Die-cast aluminium/plastic  
 Tilts 90°  
 Rotates 355°  
 Low-glare  
 Operating ambient temperature -20° to +45°  
 3,000 K or 4,000 K  
 Beam angle 15° or 40°  
 Tracks available in metre lengths  
 Beam-shaping 'barn doors' available  
 Louvre and spreader lenses available  
 Non-dimming driver included  
 Dimming driver available  
 Xicato LED technology  
 CRI (Ra) 80 or 95  
 Five-year warranty  
 LED standard lifetime 50,000 hours  
 LED luminous flux 1000 or 2000 lm  
 Fixture luminous efficacy 37 to 45 lm/W

2.0 kg  
2000 lm

2.2 kg  
1000 lm



IP 20

90°

355°

RoHS 

## Track 01



Item no.

White	15°	3,000 K	Ra 95	1000 lm	T0193010NW
			Ra 80	2000 lm	T0183020NW
	40°	4,000 K	Ra 95	1000 lm	T0194010NW
			Ra 80	2000 lm	T0184020NW
40°	3,000 K	Ra 80	2000 lm	T0183020WW	
		Ra 80	2000 lm	T0184020WW	

By special order: other combinations of beam angle + CCT + Ra + lumen