

## Track 02

---

---



Discreet, effective, flexible, all-purpose LED spotlight. Track-mounted. Choice of beam angles. Low-glare. Tilts 90°. Rotates 355°. For indoor use. For defining both collective displays and individual objects, often together. For lighting areas, rooms and surfaces. Easy installation in any ceiling. Xicato LED technology. Choice of CCT, lumen and beam angle combinations. Minimum 50% energy saving compared to equivalent halogen. Light quality ensured for entire lifetime. Rigorously tested. Rigorously documented. The light you specify is the light you get.

## Track 02

---

For indoor use/dry locations  
Track-mounted  
Die-cast aluminium/plastic  
Tilts 90°  
Rotates 355°  
Low-glare  
Operating ambient temperature -20° to +45°  
3,000 K or 4,000 K  
Beam angle 20°, 40° or 60°  
Tracks available in metre lengths  
Louvre and spreader lenses available  
Non-dimming driver included  
Dimming driver available  
Xicato LED technology  
CRI (Ra) 80 or 95  
Five-year warranty  
LED standard lifetime 50,000 hours  
LED luminous flux 1000 or 1300 lm  
Fixture luminous efficacy 49 lm/W

IP 20


90°

355°

RoHS 

## Track 02

---



Item no.

Black	20°	3,000 K	Ra 80	1000 lm	T0283010NB
		4,000 K	Ra 80	1000 lm	T0284010NB
	40°	3,000 K	Ra 80	1000 lm	T0283010MB
		4,000 K	Ra 80	1000 lm	T0284010MB
	60°	3,000 K	Ra 80	1300 lm	T0283013WB

By special order: other combinations of beam angle + CCT + Ra + lumen